Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	or trade mark:	Gnosjö Konstsmide	AB				
Supplier's addre	ess: -						
Model identifie	r: 7865						
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	DLS			
Light source cap-type		-					
(or other electri	c interface)						
Mains or non-mains:		MLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:		Nein	Envelope:	-			
High luminance light source:		Nein					
Anti-glare shield:		Nein	Dimmable:	Only with specific dimmers			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		800 in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	-			
On-mode power (P _{on}), expressed in W		8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,30			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer dimensions	Height Width	-	Spectral power distribution in the	See image in last page			

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	-	range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-			
			Chromaticity coordinates (x and y)	- -			
Parameters for d	irectional light s	sources:					
Peak luminous intensity (cd)		_	Beam angle in degrees, or the range of beam angles that can be set				
Parameters for LED and OLED light sources:							
R9 colour rendering index value		-	Survival factor	-			
the lumen maintenance factor		-					
Parameters for L	ED and OLED ma	ains light sources:					
displacement factor (cos φ1)		-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		-	Stroboscopic effect metric (SVM)	-			

(a)'-': not applicable; (b)'-': not applicable;