## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name  | e or trade mark: | Gnosjö Konstsmide | AB   |              |  |  |
|--|------------------|-------------------|--|--------------|--|--|
| Supplier's addre   | ess: -           |                   |  |              |  |  |
| Model identifie  | er: 3869-130     |                   |  |              |  |  |
| Type of light so   | urce:            |                   |  |              |  |  |
| Lighting techno  | logy used:       | LED               | Non-directional or directional:  | NDLS         |  |  |
| Light source cap-type  |                  | -                 |  |              |  |  |
| (or other electri  | ic interface)    |                   |  |              |  |  |
| Mains or non-mains:  |                  | MLS               | Connected light source (CLS):  | Nein         |  |  |
| Colour-tuneable  | e light source:  | Nein              | Envelope:  | -            |  |  |
| High luminance   | light source:    | Nein              |  |              |  |  |
| Anti-glare shield  | d:               | Nein              | Dimmable:  | No           |  |  |
| Product parameters   |                  |                   |  |              |  |  |
| Parameter  |                  | Value             | Parameter  | Value        |  |  |
|  |                  | General product   | 1  |              |  |  |
| Energy consumption in on-<br>mode (kWh/1000 h), rounded<br>up to the nearest integer   |                  | 7                 | Energy efficiency class  | E            |  |  |
| Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) |                  | 133 in -          | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | -            |  |  |
| On-mode power (P <sub>on</sub> ), expressed in W   |                  | 6,0               | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal  | 0,30         |  |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal                                |                  | -                 | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | <del></del>  |  |  |
| Outer  | Height           | -                 | Spectral power   | See image    |  |  |
| dimensions<br>without  | Width            | -                 | distribution in the  | in last page |  |  |
| .,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,  | Depth            | -                 |  |              |  |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)   |      | range 250 nm to 800<br>nm, at full-load                |          |  |  |  |
|--|------|--|----------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | -    | If yes, equivalent power (W)                           | -        |  |  |  |
|  |      | Chromaticity coordinates (x and y)                     |          |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |          |  |  |  |
| R9 colour rendering index value  | -    | Survival factor  | -        |  |  |  |
| the lumen maintenance factor   | -    |  |          |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |          |  |  |  |
| displacement factor (cos φ1)   | -    | Colour consistency in McAdam ellipses                  | -        |  |  |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.  Flicker metric (Pst LM) | _(b) | If yes then replacement claim (W)  Stroboscopic effect | <u>-</u> |  |  |  |
|  |      | metric (SVM)   |          |  |  |  |

(a)'-': not applicable;

(b)<sub>'-'</sub> : not applicable;