Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			io 13 with regard to energ	87 144 61 11811
Supplier's nam	e or trade mark:	OSRAM		
Supplier's addr	ess: LEDVANCE G	mbH, Parkring 33, (Garching, Germany	
Model identifie	er: AC34972			
Type of light so	ource:			
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		G13		
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneabl	e light source:	No	Envelope:	-
High luminance	e light source:	No		
Anti-glare shield:		No	Dimmable:	No
		Product para		
Parameter		Value	Parameter	Value
		General product p		T
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	С
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 100 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		6,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,40
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions	Height	604	Spectral power	See image
	Width	26	distribution in the	in last page
without	Depth	26		Page 1 /

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,382			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,80					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	Yes ^(b)	If yes then replacement claim (W)	18			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

