Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		, , ,	Ü	<i>.</i> , <i>.</i>
Supplier's name	e or trade mark:	as - Schwabe		
Supplier's addr	ess: Produktman	agement, Merkurst	r. 10, 72184 Eutingen im	Gäu, DE
Model identifie	er: 56721			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		-		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein
Colour-tuneable	e light source:	Nein	Envelope:	-
High luminance light source:		Nein		
Anti-glare shield:		Nein	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		20	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 680 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		20,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height		Spectral power	See image
dimensions without	Width	-	distribution in the	in last page
	Depth	-		Seite 1 /

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					

(a)'-': not applicable; (b)'-': not applicable;