## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

commission D sources	ELEGATED REGUI	ATION (EU) 2019/2	015 with regard to ener	gy labelling of light	
Supplier's name	e or trade mark:	PHILIPS			
Supplier's addre	ess: Customer Ca	re Philips, I.B.R.S./C	C.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL	
Model identifie	r: 9290035753				
Type of light so	urce:				
Lighting technology used:		LED	Non-directional or directional:	DLS	
Light source cap-type		GU5.3			
(or other electric interface)					
Mains or non-mains:		NMLS	Connected light source (CLS):	Yes	
Colour-tuneable light source:		Yes	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	Only with spe- cific dimmers	
		Product para	 meters	cine diffiners	
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	G	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		400 in Nar- row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	20006500	
On-mode power (P <sub>on</sub> ), ex- pressed in W		6,3	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	49	Spectral power dis-	See image	
sions without	Width	50	tribution in the	in last page	
separate control gear, light-	Depth	50	range 250 nm to 800 nm, at full-load		
J 7 G 3	I	I	, , , , , , , , , , , , , , , , , , , ,	। Page 1/3	

ing control parts and non-lighting control parts, if any (millimetre)						
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	35			
		Chromaticity coordi-	0,382			
		nates (x and y)	0,380			
Parameters for directional light sources:						
Peak luminous intensity (cd)	728	Beam angle in degrees, or the range of beam angles that can be set	37			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)<sub>'-'</sub>: not applicable;

(b)<sub>'-'</sub> : not applicable;

